



CONVECTOR

PRODUCT OPTIONS AND ACCESSORIES

- C0300/FS Lincat Convector Floor Stand for C0343M/C0343T Convection Ovens - with 4 Runners - W 660 mm
- C0300/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0343M/C0343T Convection Ovens - with 1 Shelf - W 660 mm

PRODUCT FEATURES

- 4 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status - see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time and fan speed for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished
- Side opening door
- Timer range 1 - 540 minutes
- Shelf spacing 85mm

The perfect addition to any commercial kitchen, the Touch C0343T with intuitive touch screen menu provides the wider functionality and greater control that only a touch screen can deliver.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT CONVECTOR ELECTRIC COUNTER-TOP CONVECTION OVEN

- W 660 MM - D 740 MM - 3.0 KW

MODEL: C0343T

WEIGHTS & DIMENSIONS

Width	660 mil
Depth	740 mil
Height	600 mil
Weight	68.7 kg

SHIPPING DETAILS

Ship Width	88 cm
Ship Depth	100 cm
Ship Height	81.5 cm
Ship Weight	75.57 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric
Electrical Total Amperage	13 A
Electrical Volts	230V
Electrical Total Wattage	3000 W
Electrical Kilowatts	3 kW
Electrical Phase	1-Phase

Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Capacity (Volume)	72 l
Construction Materials	Stainless Steel
Control Type	Electronic
Cooking Chamber Depth	550 mm
Cooking Chamber Height	398 mm
Cooking Chamber Width	330 mm
Cooking Rack Depth	325 mm
Cooking Rack Width	530 mm
Door Construction	Single Door
Door Hinge Type	Left Hang Hinge
Door Type	Stainless Steel With Viewing Glass
Fan Type	Bi-Directional

Full-Size Or Half-Size	Half-Size
Gastronorm Capacity	4 x GN1/1
Interior	Stainless Steel
Number Of Cooking Chambers	1
Number of Pans	4
Number of Wire Racks	4
Sheet Pan Capacity	4 x 460mm x 330mm
Type of Lighting	Halogen
Ventless Cooking Technology	No
Standard Depth Or Bakery Depth	Bakery Depth
Temperature Maximum	260 °C
Temperature Minimum	60 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 24, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

