
Slimline Autofill Countertop 5L with Built in Filtration


Bunco Bunco	
BURCO	

Water Boiler Features

- Compact 210mm width.
- Replaceable water filter provides better tasting beverages and reduces limescale buildup.
- Desired water temperature can be easily set between 98°c down to 70°c for more delicate speciality teas.
- Will dispense upto 206 cups per hour / 31 litres, with 5.7 litre rapid draw-off.
- The boilers eco-mode can be programmed to suit the location, reducing running costs and saving energy.
- Robust chrome tap, can be switched between controllable and constant flow with 170mm tap height above tray.
- Tough plastic drip tray, easy to empty and clean, with drain outlet for optional waste water connection.

Dimensions (mm)





Product Code 070012 Model no. SAF5CT EAN Barcode 5011139070012 Product type Autofill Boiler Warranty Period 2 years parts and labour

Technical Information			
Product Info:			
Filtered	Yes		
Capacity (litres)	5		
Packed Dimensions (WxDxH, mm)	300x544x615		
Drip Tray Dimensions (WxDxH, mm)	210x195x50		
Product Weight (kg)	8		
Packed Weight (kg)	10.7		
Colour	Bright Annealed Stainless Steel & Black		
Body Construction / Material	430 Stainless Steel		
Tank Construction / Material	304 grade Stainless Steel		
Trim and drip tray plastic type	PC ABS		
Tap Material type	Chrome		
Dual Function Tap	Yes		
Safety Standards test	EN60335		
Nonslip Feet	Yes		
Boil Dry cut-out	Yes		
Performance:			
Heat up Time to 98°c (minutes)	22.5		
Rapid Draw off—Litres	5.7		
Rapid Draw off—Pints	10		
Rapid Draw off—Cups	37		
Output per Hr—Litres	31		
Output per Hr—Pints	55		
Output per Hr—Cups	206		
Recovery Per min—Litres	0.5		
Recovery Per min—Pints	0.88		
Recovery Per min—Cups	3.3		
Heat up time 70°c—98°c (minutes)	6.5		
Cool down time 98°c-70°c (minutes)	376		
Standard power consumption (kW/hr)	0.12		
Installation:			
Hard wiring required	No		
UK fitted plug	Yes		
Cable length (m)	1.5		
Water feed pipe length (m)	2		
Max. water inlet pressure (bar)	8		
Element power rating	2.8		
Phase type	Single		
Nominal voltage	230V 50-60Hz		
Electrical supply current (A)	13		
Water inlet connection fitting	3/4" BSP		

Glen Dimplex Heating & Ventilation, Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF



