



SALES DESCRIPTION

- Sani-Control: guaranteed disinfection.
- Exclusive Hydroblade[™] washing arms: maximum effectiveness.
- 3-stage filtering system.

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous) range).

Hydroblade[™] washing arms

- Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.
- 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

✓ Keeps the washing water in optimal conditions to maintain constant washing performance.

Designed to last

- ✓ "Flow" opening mechanism: allows the hood to be raised with less effort
- ✓ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- Stainless steel surface filters for greater stability and resistance during intensive use



Premium warewashing

- Soft start: progressive start-up of the washing pump to protect fragile items.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- TEMPERATURE DISPLAY
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- Control panel with IP65 humidity protection.

You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

NCLUDES

- ✓ Rinse aid pump.
- 1 glasses basket.
- **OPTIONAL**
- Detergent dosing kit.
- Drainage pump with level
- sensor. Proactive tank water renewal.

✓ 1 mixed basket (plates).

1 cutlery basket.

ACCESSORIES

- Tables for pass-through dishwashers
- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm baskets
- Inserts & supplements
- Central sorting tables
- Double connection central sorting table

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Useful height: 430 mm

Cycles: 6 Cycle duration: 60 / 90 / 100 / 150 / 210" Production baskets / hour: 60 / 40 / 36 / 24 / 17

Boiler capacity: 12 l Wash tank capacity: 25 I

Consumption and savings

- ✓ Water consumption/cycle: 2.8 I
- Automatic saving mode in: 25'
- ✓ Automatic switch-off: 120'

Loading

- Pump: 1000 W / 1.33 Hp
- ✓ Tank: 2500 W
- ✓ Boiler: 9000 W
- Total loading: 10000 W

External dimensions (W x D x H)

Indated 28/11/2023 product sheet

- Prewashing tables for pass-through and rack conveyor dishwashers
 - Connecting tables for pass-through dishwashers and rack convevors
 - Reverse osmosis devices OS-140
 - Dosing equipments for AX / UX hood-type dishwashers



PASS-THROUGH DISHWASHER UX-120

Rack size 500 mm x 500 mm and door clearance 430 mm.

- ✓ Width:650 mm (Wide with handle: 725 mm)
- ✓ Depth: 755 mm (Bottom with handle: 835 mm)

✓ Height: 2000 mm / 1525 mm

Net weight: 104 kg

Wash temperature: 65°C Rinse temperature: 87°C


Crated dimensions


[n:embalaje_ancho] x [n:embalaje_fondo] x [n:embalaje_alto] [m:embalaje_ancho] Gross weight: 115 kg

AVAILABLE MODELS

	1303340	UX-120 400/50/3N	
	1303343	UX-120 220/60/3	
	1303344	UX-120B 400/50/3N	
	1303347	UX-120B 220/60/3	

* Ask for special versions availability





Sammic | www.sammic.com **Food Service Equiment Manufacturer**

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project Date Item Qty

Approved

WARE WASHING PASS-THROUGH DISHWASHER